



## Park Avenue

### STYLE SPECIFICATION SHEET: Utilizing Abrasive Action II (Tandus)

Face Construction	Imperial	Metric
CONSTRUCTION ACCUWEAVE®	Patterned Loop	
FACE WEIGHT	24 oz/sq yd	813.6 g/sq m
GAUGE	1/12	47.2 rows/10 cm
STITCHES PER INCH	8.0 31.5 pu/10 cm	
PILE HEIGHT AVERAGE	0.187 inch	4.7 mm
FIBER SYSTEM	TDX Nylon	
DYE METHOD	100% Solution Dyed	
SOIL/STAIN PROTECTION	Ensure	15.8 Kilotex
PRIMARY TUFTING SUBSTRATE	Synthetic Non-Woven	
PATTERN MATCH	N/A	

### Third Party Environmental Certifications

Product	Recycled Content*		NSF 140 SCS Certified
	Overall	Post-Consumer	
CERTIFIED ER3® MODULAR	45-67%	20%	Platinum
CERTIFIED ETHOS® MODULAR	26-52%	20%	Platinum
CERTIFIED POWERBOND® CUSHION	7-32%	7%	Gold
CERTIFIED FLEX-AIRE® CUSHION MODULAR	21-40%	4%	Gold
CERTIFIED POWERBOND® MEDFLOOR®	7-31%	7%	

\*Minimum recycled content certified by Scientific Certification Systems (SCS) and varies by product style.

### Product Testing/Information

ANTIMICROBIAL CHEMICALS	No antimicrobials (EPA Registered pesticides) added to product (ASTM E2471-05)
ELECTROSTATIC PROPENSITY	1.5 kV (AATCC 134); Permanent Conductive Fiber
SURFACE FLAMMABILITY	Passes CPSC FF 1-70 (ASTM D-2859)
FLOORING RADIANT PANEL	Class 1 (mean average CRF: 0.45 w/sq cm or higher) (ASTM E-648)
SMOKE GENERATION	Less than 450 (ASTM E-662)

### Installation Methods

WET SPREAD	Backing specific Tandus Adhesives
INSTALLATION METHOD	Monolithic, Random

### Product Notes

1. Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice. Colors may vary slightly from dye lot to dye lot.
2. U.S. Patent numbers: 4,849,297; 4,49,267; 5,728,741; 5,855,981; 5,914,353; 6,406,574