



Time Square

PRODUCT SPECIFICATIONS		
PRODUCT COMPOSITION	STANDARD / NORMS	DATA
Manufacturing Process	DIN 61151	Needle felt
Surface Aspect	ISO 2424	Hobnail (Berber) pattern
Fiber	CEE 83/623	100% Solution dyed UV Stabilized polypropylene fibers
Primary Backing	ISO 2424	High Density Rubber
CERTIFICATIONS		
	ISO 9001:2008	Quality Management Systems
	CRI Green Label Plus	GLP1705
PRODUCT DIMENSION		
Pile Height (+ or - 0.5 mm)	ISO 1765	.25 inch
Total Height (+ or - 7.5%)	ISO 1765	.50 inch
Pile Weight (+ or - 7.5%)	ISO 8543	54 oz/sy
Total Weight (+ or - 7.5%)	ISO 8543	78 oz/sy
Roll Size (+ or - 2%)	ISO 3018	6'7" x 82' or 13'2" x 82'
Custom		Special sizes and logo mats
ELECTROSTATIC PROPERTIES		
Dimensional Stability	EN 986	Pass
Walk on Test	ISO TR 6356	>2kV
Electrical Resistivity	IBM / ICL	Pass, for R.H. > or = 40%
Sound Insulation	ISO 140-8	> or = 21dB
Thermal Retention	ISO 11092	0.15 m K/W Pass
COLOR FASTNESS		
To Light	ISO 105 B02	5
To Water	ISO 105 E01	5
To Shampoo	BS 1006	4 - 5
To Rubbing dry & wet	ISO 105X12	Dry 4 Wet 3 - 4
FLAMMABILITY RATING		
Radiant Panel Test	ASTM E648 / DIN 4102	Passes Federal Flamm. Standard
Pill Test	ISO 6925 / ASTM D2859	Pass
Hot Metal Nut Test	BS 4790/BS 5287	Pass
LEED		
MR Credit 4	LEED-NC v. 3 For 1 - 2 points: \$ value of all	15% recycled post consumer
IEQ Credit 4.1	LEED-NC v. 3 For 1 point: low-emitting adhesive with a VOC of 50 g/l or less for indoor releasable carpet adhesive	Releasable VOC 0 g/l
IEQ Credit 4.3	LEED-NC v. 3 For 1 point: Low-Emitting Materials- Flooring Systems	Green Label Plus certified
IEQ Credit 5	LEED-NC v. 3 For 1 point: semi-permanently installed entrance system at least 10' in length and maintained on a weekly basis.	This carpet is a semi permanent installation