



Metropolitan Super Abrasive Matting

Product Specs

Page 1

Powerbond ethos® Cushion

Reclamation	100% recyclable in the ReStart® Program
Product Size	6' Roll 1.8 m
Total Recycled Content	44.6% (.0% Pre-Consumer; 44.6% Post-Consumer)
Warranty Information	7 Year
Total Product Thickness	0.297 in (7.5438 mm)
Platform Sizes	Unlimited Free Lay 18" x 18", 36" x 36", 6' Roll, 24" x 24" Tile
Pattern Scale	Small
Pattern Type	Linear
Collection	Metropolitan Super Abrasive - Assertive
Coordinating Group	Textures
Primary Backing	Non-woven synthetic fiber
Construction	Stratatec® Patterned Loop
Recycled Content	Yes
Face Weight	28 oz/sq yd 949.2 g/sq m
Gauge	5/64 50.4 rows/ 10 cm
Stitches Per Inch	9.0 stitches / inch 35.4 stitches/10cm
Pile Height Average	.187 inch 4.7 mm
Fiber System	TDX® Nylon
Dye Method	Solution Dyed
Soil/Stain Protection	Ensure



Metropolitan Super Abrasive Matting

Product Specs

Page 2

ER3 Note	Recycled content percentages are third-party certified annually based on the prior year's formulations and use. Recycled content specifications may be changed without notice when formulations are modified due to, for example, new manufacturing capabilities, environmental efficiencies, or postconsumer market availability.
Pattern Match	Not Required
Colorfastness to Light	> 4 after 100 hours (AATCC 16E)
Fluorine	Minimum 500 ppm (CRI TM-102).
Third Party Certification NSF-140	Platinum
CRI Green Label Plus Certification	GLP8320
Antimicrobial Chemicals	No antimicrobials (EPA Registered pesticides) added to product (ASTM E2471-05)
Electrostatic Propensity	1.0 kV (AATCC 134); Permanent Conductive Fiber
Surface Flammability	Passes CPSC FF 1-70 (ASTMD-2859)
Flooring Radiant Panel	Class 1 (mean average CRF: 0.45 w/sq cm or higher) (ASTM E-648)
Smoke Generation	Less than 450 (ASTME-662)